

● Reel type / for ferrule end-faces of connector plug

CLETOP-S

replacement cartridge



- TypeA (2.5mm)
- TypeB (1.25mm, flat)



Easy to replace tape cartridge

The tape can be replaced very easily by a "drop-in" cartridge.



One push operation

Available for both left hand and right handed operators.

Anti-static propeties

Has excellent anti-static properties for static sensitive applications and can avoid reattachment dust to the ferrule after cleaning and it can avoid reattachment of dust after cleaning.

◆ Specification of CLETOP - S


Ferrule	ø2.5mm	ø1.25mm
Type	Type A	Type B
Part No.	14110501	14110601
Shape of rubber pad		
Cleans per cartridge	more than 400 times	more than 400 times
Connectots cleaned	SC, SC2, FC, ST, DIN, D4	MU, LC, MT, MPO, MT-RJ without pins, Biconic
Dimension W x H x D mm	125 x85 x 35	
Weight (g)	150	150
Packaging	1	1
Remarks	-	-

Consumables	Replacement cartridge blue (6 pcs/set)	Replacement cartridge white (6 pcs/set)
Part No. of	14110700	14010710


cosumable		
-----------	--	--

Notice1: Please do not use this product for other purposes than cleaning the ferrule end-faces.
 Notice2: The cleaning performance may change depending upon the environment and the contamination types.

Ultra-fine Micro-fibers deliver outstanding cleaning performance in contamination.




Ferrule end-faces before / after use of the CLETOP series.





mechanism of cleaning MPO/MT-RJ connectors with pins.

- mechanism of cleaning the multi-fiber pinned connectors



The cleaner for ribbon connector with pins has joined the current CLETOP series.



Test Time	Return Loss (-dB)		
	Before applying dust	After applying dust	After Cleaning
1	60.9	29.5	61.8
2	61.2	12.1	58.7
3	59.2	11.6	60.3
4	60.3	11.6	57.3
5	58.1	24.8	60.3
6	61.5	11.6	55.5
7	61.4	14.7	57.9
8	58.2	25.7	58.8
9	59.7	11.5	59.3
10	59.4	16.5	57.9
ave	60.0	17.0	58.8